

[First Hit](#)[Previous Doc](#)[Next Doc](#)[Go to Doc#](#)Generate CollectionPrint

L2: Entry 2 of 8

File: JPAB

Jan 16, 2001

PUB-NO: JP02001010222A

DOCUMENT-IDENTIFIER: JP 2001010222 A

TITLE: INK-JET RECORDING MATERIAL HAVING PIGMENT LAYER

PUBN-DATE: January 16, 2001

INVENTOR-INFORMATION:

NAME

COUNTRY

BARCOCK, RICHARD

DODDS, ALASTAIR

WERNER, KIRSTEN

BECKER, DIETER

ASSIGNEE-INFORMATION:

NAME

COUNTRY

FELIX SCHOELLER JR FOTO & SPEZIALPAPIERE GMBH & CO KG

APPL-NO: JP2000130432

APPL-DATE: April 28, 2000

PRIORITY-DATA: 1999EP-108448 (April 30, 1999)

INT-CL (IPC): B41 M 5/00; B41 J 2/01

ABSTRACT:

PROBLEM TO BE SOLVED: To obtain a recording material having a high ink absorption capacity, a short drying time, and good abrasion resistance by forming a pigment layer arranged on a support material from a lower layer containing barium sulfate and an upper layer containing aluminum oxide as a main pigment.

SOLUTION: In a recording material having a support material and a pigment layer formed on the support material, the pigment layer is formed from a lower layer containing barium sulfate and an upper layer containing aluminum oxide as a main pigment, or containing a mixture of at least two pigments. In the lower layer, besides barium sulfate as a main pigment, aluminum oxide, silica, barium oxide, and others can be contained additionally. The average particle size of the pigments is set up at 0.7-5 μ m. Gelatin as a binder can be contained in the lower layer.

COPYRIGHT: (C)2001,JPO

[Previous Doc](#)[Next Doc](#)[Go to Doc#](#)